



KOMROWSKI

M/V "ADRIAN"

TYPE:	SELSUSTAINED CELLULAR CONTAINERVESSEL - B 170		
CLASS:	GERMANISCHER LLOYD +100 A5 CONTAINERSHIP IW, SOLAS II-2 REG. 54, NAV-O +MC AUT		
BUILT:	6/1997 AT STOCZNIA SZCZECINSKA S.A., SZCZECIN		
TONNAGE:	INTERNATIONAL	16,800	8,672 GRT / NRT
	SUEZ	17,201	14,445 GRT / NRT
	PANAMA	---	/ 15,114 PC/UMS
DWAT/DRAFT:	22,984 MTS ON 9.905 SSW DRAFT		
DIMENSIONS:	LENGTH OVER ALL	184.10M	
	BREADTH MOULDED	25.30M	
	LENGTH BETWEEN PP	172.36M	
	DEPTH	13.50M	
FLAG:	LIBERIA		

CONTAINERS: ALL INTAKES ARE ALWAYS SUBJECT TO VESSEL'S TRIM, STABILITY, DEADWEIGHT, PERMISSIBLE WEIGHTS, PERMISSIBLE LASHING GEAR, BREAK LOADS, CONTAINER LASHING PLAN, RANGES OF VISIBILITY, PANAMA/SUEZ REGULATIONS AND OSHA RULES IN WHICH CASE INTAKES AND STACKWEIGHTS CAN BE CONSIDERABLY REDUCED.

	on deck	in hold	total
20'	1,096TEU	634 TEU	1,730 TEU
40'+20'	520 FEU + 48 TEU	305 FEU + 24 TEU	825 FEU + 72 TEU
Reefer	300 plugs	-	300 plugs
40' High Cubes	426 units	236 units	662 units
45'	212 units	-	212 units
40' pallet wide 2.50 m	104 units	305 units	409 units
Homo intake bss 14 mts			1,120 TEU



KOMROWSKI

	INTAKE PANAMA CANAL RANGE OF VISIBILITY: 1,582 TEU UP TO 212 UNITS OF 45' LENGTH RESPECTIVELY 80 UNITS OF 48' LENGTH MAY BE STOWED ON DECK POSSIBLE STOWAGE IN HOLDS: FOUR TIERS 8'6" PLUS ONE TIER 9'6" EXCEPT HATCH NO. 2				
CONTAINER FITTINGS:	FULLY CELLULARIZED IN HOLDS FOR 40' UNITS. ALTERNATIVELY 2 x 20' UNITS CAN BE STOWED INTO EACH 40' COMPARTMENT. FITTED WITH LOOSE LASHINGS FOR 20'/40'/45'/48' UNITS.				
REEFER:	440V, 60 HZ, 3 PHASES 3 O'CLOCK				
STACK LOADS:	20'	40'	45'	48'	
TANKTOP	140 MTS	175 MTS	--	--	
MAIN DECK:	75 MTS	120 MTS	--	--	
HATCHES 1,2:	40 MTS	60 MTS	--	--	
HATCHES 3-9:	60 MTS	90 MTS	90 MTS	90 MTS	
4 HO/9 HA:	HATCH NO 1: 12.48 X 13.00 M - COVERED BY 1 PONTOON HATCH NOS 2-9: 12.48 X 20.60 M - COVERED BY 2 PONTOONS				
HATCH COVERS:	PONTOON TYPE HATCH COVERS DEVIDED INTO TWO LONGITUDINAL SECTIONS WHICH CAN BE OPENED IN UNCONSTRAINED SEQUENCE, EXCEPT HATCH NO. 1 WHICH IS A SINGLE PONTOON				
CRANES:	3 X 40 MTS SINGLE CRANES, OUTREACH ABT. 28M				
TANK CAPACITY:	IFO ABT 2,184 CBM - MDO ABT 165 CBM WATERBALLAST 7,867 CBM				
MAIN ENGINE:	SULZER 6 RTA 62U OF 13,320 KW AT 113 RPM				
AUXILLARIES:	3 x SULZER 9S20H OF 1,540 KVA AT 900 RPM				



KOMROWSKI

SPEED/

CONSUMPTION: ABT 20 KNOTS ON ABT 54,5 MTS IFO AT DESIGN DRAFT OF 9.75M BASIS CLEAN AND SMOOTH BOTTOM, EVEN KEEL, DEEP AND CURRENTLESS WATER/SEA WITH A TEMPERATURE OF MAX 28 DEGREES CELSIUS, WIND MAX BEAUFORT 2 AND SEA NOT EXCEEDING DOUGLAS SEA STATE 2. NO MDO AT SEA EXCEPT IN CASE OF EMERGENCY. CHARTERERS TO PROVIDE SUFFICIENT QUANTITY OF MDO DURING SEA PASSAGES FOR OPERATING AUXILIARIES/GENERATORS IN CASE OF EMERGENCY.

NOTWITHSTANDING ANYTHING ELSE CONTAINED IN THIS CHARTER PARTY, THE CHARTERERS SHALL SUPPLY FUELS OF SUCH SPECIFICATION AND GRADES TO PERMIT THE VESSEL, AT ALL TIMES, TO MEET THE MAXIMUM SULPHUR CONTENT REQUIREMENTS OF ANY EMISSION CONTROL ZONE WHEN THE VESSEL IS TRADING WITHIN THAT ZONE. THE CHARTERERS SHALL INDEMNIFY, DEFEND AND HOLD HARMLESS THE OWNERS IN RESPECT OF ANY LOSS, LIABILITY, DELAY, FINES, COSTS OR EXPENSES ARISING OR RESULTING FROM THE CHARTERERS' FAILURE TO COMPLY WITH THIS CLAUSE. FOR THE PURPOSE OF THIS CLAUSE, "EMISSION CONTROL ZONE" SHALL MEAN ZONES AS STIPULATED IN MARPOL ANNEX VI AND/OR ZONES REGULATED BY REGIONAL AND/OR NATIONAL AUTHORITIES SUCH AS, BUT NOT LIMITED TO, THE EU AND THE U.S. ENVIRONMENTAL PROTECTION AGENCY.

PORT

CONSUMPTION: ABT. 5.0 MTS IFO DAILY INCL. CRANES
ABT. 3.0 MTS MDO DAILY WHEN IDLE

ALWAYS EXCLUDING REEFERS AND VENTILATION PLUS SOME IFO FOR HEATING FUEL OILTANKS.

FUEL

SPECIFICATION: ISO STANDARD 8217:2005(E) OR ANY SUBSEQUENT AMENDMENT THEREOF CLASS 'RMG35' OR BETTER (FOR IFO) AND CLASS 'DMB' OR BETTER (FOR MDO). THE PRODUCT MUST BE COMPOSED OF STRAIGHT MINERALS ONLY AND FIT FOR USE IN VESSEL'S ENGINES WITHOUT ANY CHEMICALS, WASTE LUBRICANTS OR ANY OTHER HARMFULSUBSTANCES. FUELS TO BE SUPPLIED BY



KOMROWSKI

CHARTERERS WITHIN SPECIFIED CCAI LIMITS OF ENGINE MAKER, BUT NOT EXCEEDING CCAI VALUE OF MAXIMUM 850.

BUNKERS OF DIFFERENT GRADES/QUANTITIES/SUPPLIERS NOT TO BE MIXED.

SLUDGE REMOVAL, IF ANY, TO BE FOR CHARTERER'S ACCOUNT AND TIME.

THE VESSEL WILL PARTICIPATE IN THE FOBAS FUEL QUALITY TESTING PROGRAM. SAMPLES WILL BE TAKEN DURING EACH BUNKERING. COSTS INVOLVED IN THE AMOUNT OF USD 300.- PER SAMPLE TO BE EQUALLY SHARED BETWEEN OWNERS AND CHARTERERS.

FITTINGS:

SUEZ, PANAMA, WWF/AUSTRALIA REGULATION, GMDSS, SATELLITE COMMUNICATION (TELEPHONE/TELEX/FAX), ANTI HEELING INSTALLATION:

PUMP CAPACITY 450 CBM/HR.

THE VESSEL IS EQUIPPED WITH A BOWTHRUSTER (750 KW) WITH SUCTION TUNNEL WHICH IS AT CHARTERERS DISPOSAL, HOWEVER, OWNERS ARE NOT RESPONSIBLE FOR MAL-FUNCTIONING OF THE UNIT AND/OR CONSEQUENCES THEREOF

SPECIAL FEATURES:

CAPABLE OF CARRYING IMO CARGO UNDER DECK:

HOLD 1: IMDG 1,2,3,4,5,1,6,1,8

HOLDS 2-4: IMDG 1.4S,2,3,4,5,1,6,1,8

(IMO CLASSED CARGO(ES) ALWAYS TO BE LOADED IN STRICT CONFORMITY WITH IMO AND LOCAL SAFETY REGULATIONS AS WELL AS IN ACCORDANCE WITH THE VESSEL'S CERTIFICATE OF COMPLIANCE FOR THE CARRIAGE OF DANGEROUS GOODS.)

ELECTRICALLY VENTILATED HOLDS: 6 AIRCHANGES/ HOUR BASIS
EMPTY HOLDS - CO₂ FITTED INCLUDING SMOKE DETECTOR IN CARGO HOLDS AND ENGINE ROOM

CAPABLE OF CARRYING BREAKBULK CARGO IN HOLD NOS. 2,3 AND 4 ON TANKTOP AREAS WITH UPTO 3 LAYERS OF 40'x8'6" CONTAINERS OF 30 MTS EACH ON TOP OF HINGED STOPPERS



KOMROWSKI

(ALL DETAILS ABOUT, GIVEN IN GOOD FAITH BUT WITHOUT
GUARANTEE)
